

## Description:

The Brandolino Spike is a fix glowing low glare fixture ideal for ambience lighting in planter beds and greenery. Supplied with a CREE XLamp XP-G3. Available in various colour temperatures and finishes. IP65, Frosted acrylic diffuser, pre-fitted 500mm lead.



## Technical:

LED TYPE	CREE XLAMP XP-G3	CONTROL GEAR	REMOTE
RATED POWER	1W - 3W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SPIKE
INPUT POWER / FORWARD VOLTAGE	3V DC 350ma CONSTANT CURRENT	WEIGHT	ON REQUEST
NOMINAL LUMENS	90-180lm	HARDWARE	FROSTED ACRYLIC DIFFUSER, CABLE
IP RATING	IP65	CONSTRUCTION	MACHINED METAL
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

## Product Generator: example 1604-AB-M-30-SP-1W-ON/OFF-N/A

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL1610	AB Aged Brass	N Narrow 10°	27 2700K	SP Spike	1W / 350ma	On/Off*	N/A
	BR Brushed Brass	M Medium 21°	30 3000K		3W / 700ma		
	PB Black	W Wide 33°	40 4000K				
	PW White						
	CC Custom						

\*Dimming available on request

NL1610	-	-	-	-	-	-	-
--------	---	---	---	---	---	---	---