

Description:

Belonging to the **Firefly Family** range, the Fire Deco Pendant offers a simple, clean aesthetic with a decorative feature available in various colour temperatures, options and control options. The products contain the same LED chip and options for a consistent approach. Supplied with matching ceiling rose and cable in 3 standard drop lengths of 150mm, 350mm and 500mm. The Family also consists of a **Micro**, **XL** and **Firefly Standard** range creation of products.



Technical:

LED TYPE	XHP-50 Gen 2	CONTROL GEAR	REMOTE
RATED POWER	4W - 6W - 9W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SURFACE MOUNTED
INPUT POWER	350mA - 700mA - 1050mA / 6V	WEIGHT	1-2KG
NOMINAL LUMENS	300lm - 476lm - 780lm	HARDWARE	GLAND, CABLE
IP RATING	IP65	CONSTRUCTION	MACHINED METAL & HEATSINK
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

Product Generator: example 7038-BR-M-30-1-4W-1-1

Model	Finish	Beam Angle	CCT	Moun	Wa age	Dimming	Accessory
NL7038	AB Aged Brass	N Narrow 10°	27 2700K	1 Suspended 150mm	4W / 350mA	DALI	HC Honeycomb Louver
	BR Brushed Brass	M Medium 21°	30 3000K	2 Suspended 350mm	6W / 700mA	0-10V	DL Di user Lens
	PB Black	W Wide 33°	40 4000K	3 Suspended 500mm	9W /1050mA	Phase	EL Elliptical Lens
	PW White			4 Suspended custom		On/O	SL Spread Lens
	CC Custom						WS Wire suspension

NL7038	-	-	-	-	-	-	-
--------	---	---	---	---	---	---	---