

## Description:

Architectural, a member of the Firefly family, Firefly Pendant offers a simple clean aesthetic available in various colour temperatures, optics, finishes and control options. Firefly Pendant shares the technical features of the remainder of the Firefly family ensuring consistent illumination whilst being controllable for the desired ambiance. A luminaire which provides sought after energy efficiency and product longevity.



## Technical:

LED type	XHP-50 Gen 2	Control gear	Remote
Rated power	4W – 6W – 9W	Dimming protocols	Dali, 0-10V, Phase Dim, On/Off
CRI	80	Cable length	300 mm
Beam angles	Nominated in table below	Mounting options	Surface mounted
Input power/Forward voltage	350mA - 700mA – 1050mA/6V	Weight	0.6 kg
Nominal lumens	300lm - 476lm – 780lm	Hardware	Glass lens, Gland, Cable
IP rating	IP65	Construction	Machined metal, heatsink
Colour temperature	2700K – 3000K – 4000K	Warranty	Two years

## Product Generator: example NL-7008-PW-M-30-SM10-6W-3-DL

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessories
NL-7008	AB Aged brass	N Narrow 10°	27 2700K	SM5. Drop 500 mm	4W/350mA	1 Dali	HC Honeycomb louver
	BR Brushed brass	M Medium 21°	30 3000K	SM10. Drop 1000 mm	6W/700mA	2 0-10V	DL Diffuser lens
	PB Black	W Wide 33°	40 4000K	SM15. Drop 1500 mm	9W/1050mA	3 Phase	EL Elliptical lens
	PW White			SMXX Drop Custom mm		4 On/Off	SL Spread lens
	CC Custom						RS Rod Suspension

## Order Code

NL-7008							
---------	--	--	--	--	--	--	--